

Providing Solutions in Pressure Sensitive Films

Product Construction Sheet

FLEX-Vu® OL 300 CLEAR VELVET L-29 142PolyC-9

GENERAL DESCRIPTION:

This is a clear velvet embossed polycarbonate film coated with a clear overlaminating pressure sensitive acrylic adhesive and backed with an ultra smooth super clear polyester release liner.

UL RECOGNITION:

This product is UL recognized for indoor use with occasional exposure to lubricating oil and water. For further information, please reference FLEXcon's UL file No MH10170 (N) or contact your FLEXcon Representative.

PRODUCT DATA VALUE TEST METHOD

PHYSICAL PROPERTIES

Thickness Film: 75 +/- 10 % (micron) Adhesive: 36-38 +/- 3

Liner: 36 +/- 10 %

Dimensional Stability (%)

No shrinkage observed

On Al panel at 70 C for 24 hr.

ADHESION PROPERTIES**

Adhesion from

(N/m) Average
Stainless Steel 803

Acrylic 836 Glass 869

Expected Shear 100 + FTM 8

(hours)

Tack (gm/sq cm) 360 ASTM D 2979

** For guidance only

This data is based on limited test results due to the custom nature of this product, not to be used for setting specifications.

EXPECTED EXTERIOR LIFE	Indoor use only
SERVICE TEMPERATURE RANGE	-40°C to 100°C
MINIMUM APPLICATION TEMPERATURE	10`C
STORAGE STABILITY	Two years stored at 21°C and 50% RH

^{*} FLEX-Vu is a registered trademark of FLEXcon Company, Inc.

15/08/2002

ASTM D 3652

FTM 1 (Modified for

72 hr dwell time)

Product Performance and Suitability

All of the descriptive information, the typical performance data, and recommendations for the use of FLEXcon products shall be used only as a guide and do not reflect the specification or specification range for any particular property of the product. Furnishing such information is merely an attempt to assist you after you have indicated your contemplated use and shall in no event constitute a warranty of any kind by FLEXcon. All purchasers of FLEXcon products shall be responsible for independently determining the suitability of the material for the purpose for which it is purchased. No distributor, salesman, or representative of FLEXcon is authorized to give any warranty, guaranty, or make any representation in addition or contrary to the above.