

SK88 Series

Zero Transfer Security label



PRODUCT DESCRIPTION

Traces of prints or patterns are non-transferred to substrates when the tape is removed. Excellent tamper evident performance.

CHARACTERISTICS

This product leaves no unsightly or sticky deposit whilst clearly showing that it has been tampered with. This unique adhesive system exclusive to Seal King is ideal where packaging has to be re-used or where the continued aesthetics of the package are integral to the overall product appearance.

TYPICAL APPLICATIONS

Ideally suitable to be used as security seals on metal, glass and high energy plastic surfaces for pharmaceutical, automobile industries; forensic science, aviation, transportation & banking security, electronic, cosmetic & luxury goods warranty etc.

TECHNICAL DATA

180°C Peel Adhesive for VOID:

9.76~13.66N/2,5cm: PSTC-1

Total Thickness: 0.09~0.10mm

Initial Tack:

< 10cm *PSTC-6 #14 ball*

Holding Power:

0.5kg/25mm x 25mm :

>72hrs *PSTC-7*

Holding Power for temperature

Resist 60°C:

0.5kg/25mm x 25mm :

>24hrs *PSTC-7*

SIZE

48~480mm, length: 50~500m

COLOR

Red, blue, white, black.
Other colours on request.

LINER

White double PE single silicon glassine paper.

CARRIER

PET matt

VOID TEMPERATURE

Temperature: -10°C~ +40°C;
Relative humidity: 55% +/-10%

RECOMMENDED OPERATING TEMPERATURE

+10°C ~ +35°C

VOID MESSAGE

Standard VOID print

PERSONALISED VOID MESSAGE

Subject to discussion

ADDITIONAL PRINTING

Available upon request, sequential numbering, bar codes etc. Can be signature written with indelible pen/ ink for additional personalised security.

AVAILABLE FORMATS

Jumbo rolls, log rolls, slit rolls, die cuts on roll.

SHELF LIFE

1 year under normal condition. Avoid exposing to high humidity and direct sunlight.




HOW TO APPLY

When applying the tape the surfaces to be bonded should be dry, dust &

Multifoil products are produced under stringent manufacturing process and quality control conditions. The information and typical values provided are based upon research believed to be reliable and are provided without guarantee and do not constitute a warranty. Purchasers should determine the suitability of the products prior to its intended use.

Product liability – Terms of sale – article 8

Version July 2014





grease free and thoroughly clean. Avoid touching the exposed adhesive surface of the tape as this impairs the performance. The adhesive used on these tapes are pressure sensitive, so always ensure sufficient pressure is applied to the tape evenly over the whole surface to ensure the best bonding results.

